

# YUCON FLOOR COVERING

<b>tipo produzione</b> manufacturing process método de fabricación méthode de fabrication	agugliato needlefelt punzonada aiguilleté
<b>composizione - composition</b> composición - composition	100% PP
<b>fondo - backing</b> soporte - dossier	schiuma gel gofrato - wafel backing espuma gel gofrado - mousse de gel gaufré
<b>peso filato - pile weight</b> peso fibra - poids poil	1.790 g/m <sup>2</sup>
<b>peso totale - total weight</b> peso total - poids total	2.950 g/m <sup>2</sup> +/-15%
<b>spessore fibra - pile height</b> espor pelo - épaisseur poil	5,5 mm
<b>spessore totale - total height</b> espor total - épaisseur total	11 mm
<b>lunghezza rotoli</b> size of the rolls medida piezas dimension des pièces	23 ml
<b>altezza rotoli - width</b> ancho - largeur	100/200 rotoli o taglio - rolls or cut rollos o corte - rouleaux ou coupe
<b>destinazione</b> use utilización utilisation	EN 685 classe d'uso: 23, traffico medio, ingressi, locali pubblici, abitazioni EN 685 use class: 23, medium traffic, entrances, public buildings, houses EN 685 clase de utilización: 23, medio tráfico, entradas, locales públicos, viviendas EN 685 classe d'utilisation: 23, trafic moyen, entrées, locaux publics, habitations

